



## **Αντλίες T Rubber impeller** **RUBBER IMPELLER PUMPS - T SERIES**

Manufacturer: Enoveneta

### **Introduction**

Enoveneta's rubber impeller pumps are built entirely of AISI 304 stainless steel, and are available with flow rates from 80 to 300 hectolitres per hour.

All models are equipped with a rubber impeller, by-pass and electric control panel with reverse drive.

Various accessories are available, such as a radio control, liquid presence probe and inverter.



RUBBER IMPELLER PUMPS - T SERIES

## T SERIES PUMPS

### Standard features

- AISI 304 stainless steel stand
- AISI 304 stainless steel pump body
- EPDM Food-safe rubber impeller
- By-pass (excluding T100 model) **2**
- Single-speed electric motor (T40)
- Two-speed electric motor (T60, T80)
- 400/3/50 control panel with reverse feature

### Optionals

- Electronic speed variator with remote cable control **3**
- Electronic speed variator with remote radio control **1**
- Liquid detection probe
- Electric panel for pumping over with recycle time relay
- Selector for automatic operation from remote control for pumps with inverter

## Αντλίες T Rubber impeller

### RUBBER IMPELLER PUMPS - T SERIES

Manufacturer: Enoveneta



By-pass



Electronic speed variator with remote cable control



Electronic speed variator with remote radio control



## Technical data

|                        |     | T40<br>1 VEL | T40<br>INV | T60<br>2 VEL | T60<br>INV | T80<br>2 VEL | T80<br>INV | T100<br>INV |
|------------------------|-----|--------------|------------|--------------|------------|--------------|------------|-------------|
| Motor power            | kW  | 1.1          | 1.1        | 1.5/2.2      | 2.2        | 2.2/3.0      | 3.0        | 4.0         |
| Flow rate              | l/h | 80           | 25/80      | 100/190      | 6/190      | 170/300      | 23/300     | 60/500      |
| Min/Max head           | m   | 20/25        | 20/25      | 20/25        | 20/25      | 20/25        | 20/25      | 20/25       |
| Revolutions per minute | rpm | 900          | 180/900    | 380/760      | 150/760    | 380/760      | 150/760    | 150/760     |
| Fittings               | DIN | 40           | 40         | 65           | 65         | 80           | 80         | 100         |
| Length                 | mm  | 700          | 700        | 840          | 840        | 860          | 860        | 1050        |
| Depth                  | mm  | 300          | 300        | 430          | 430        | 430          | 430        | 500         |
| Height                 | mm  | 500          | 500        | 730          | 730        | 730          | 730        | 730         |
| Weight                 | K   | 27           | 32         | 61           | 65         | 70           | 70         | 90          |

Measurements and operating data are not legally binding and subject to change without notice.